

## Cam follower CR24-B-IKO - CR24-B-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cr24-b-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.)	Boundary dimensions mm (inch)						Bearing dimension $f$ mm (inch)	Maximum spinning torque $C$ N·m	Basic dynamic load rating $C_0$ N	Basic static load rating $C_0$ N							
	Shield type		Sealed type			$g$	$D$	$C$	$d_1$	$G$	$G_1$											
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring																		
15.875 ( $\frac{5}{8}$ )	CR 24 B				225	38.100 ( $1\frac{1}{2}$ )	22.225 ( $\frac{7}{8}$ )	15.875 ( $\frac{5}{8}$ )	$F_1-18$	19.050 ( $\frac{3}{4}$ )	23.8 (0.93)	38.100 ( $1\frac{1}{2}$ )	9.525 ( $\frac{3}{8}$ )	0.794 ( $\frac{1}{16}$ )	4.702 ( $\frac{1}{8}$ )	3.969 ( $\frac{1}{8}$ )	7.938 ( $\frac{1}{4}$ )	1.588 ( $\frac{1}{16}$ )	25.195 ( $1\frac{1}{8}$ )	55.7	19.000	24.300

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952460314
Inside diameter	15.875 mm
Outside diameter	38.1 mm
Thickness	22.225 mm
Weight	225 g
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE