


Cam follower CR30-BUUR-IKO - CR30-BUUR-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cr30-buur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G UNF | G ₁ |
|-----------------------------|----------------------------|--------------------------------|----------------------------|--------------------------------|---------------------|----------------|-------------|--|---|--|
| | Shield type | | Sealed type | | | | | | | |
| | With covered outer ring | With cylindrical outer ring | With covered outer ring | With cylindrical outer ring | | | | | | |
| 19.050 (3/4) | CR 30 BUUR | | | | 410 | 47.625 (1 7/8) | 25.400 (1) | 19.050 (3/4) | 7/16 | 22.225 (7/8) |
| Boundary dimensions mm/inch | | | | | | | | | | |
| B max | B ₂ | B ₃ | C ₁ | E ₁ | E ₂ | H | r | Bearing dimension f Mm (mm/inch) | Maximum tightening torque C N·m | Basic static load rating C ₀ N |
| 25.8126 | 44.650 (1 3/4) | 11.112 (3/4) | 0.794 (1/8) | 4.792 (3/4) | 3.969 (3/8) | 7.938 (3/4) | 1.988 (3/8) | 32.543 (1 1/4) | 100 | 25 100 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060462695 |
| Inside diameter | 19.05 mm |
| Outside diameter | 47.625 mm |
| Thickness | 25.4 mm |
| Weight | 410 g |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE