


Cam follower CR26-IKO - CR26-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cr26-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
15.875 (5/8)	CR 26				260	41.275 (1 1/2)	22.225 (7/8)	15.875 (5/8)	1 1/8	19.050 (3/4)
Boundary dimensions mm(inch)										
B _{max}	B ₂	B ₃	C ₁	δ ₁	δ ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
23.8 (9/16)	38.100 (1 1/2)	9.525 (3/8)	0.794 (1/16)	4.762 (3/16)	3.969 (1/8)	1.588 (1/16)	26.196 (1 1/16)	55.7	10 800	24 300

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463005
Inside diameter	15.875 mm
Outside diameter	41.275 mm
Thickness	22.225 mm
Weight	260 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE