

Cam follower CR22-V-IKO - CR22-V-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cr22-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inchi)	Identification number				Mass (Ref.)					
	Shield type With cover With cylindrical outer ring		Sleeved type With cylindrical outer ring		ϕ	D	C	d_1	G UNF	G_1
12.700 ($\frac{1}{2}$)	CR 22 V				160	34.925 ($1\frac{1}{4}$)	19.050 ($\frac{3}{4}$)	12.700 ($\frac{1}{2}$)	$\frac{1}{4}$ -20	15.875 ($\frac{5}{8}$)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N		
B max	B_2	B_3	C_1	g_1					g_2	r
28.4 (1.118)	21.750 ($\frac{7}{8}$)	7.938 ($\frac{5}{16}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	1.588 ($\frac{1}{16}$)	21.628 ($\frac{7}{8}$)	27.7	22 800	31 700

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463791
Inside diameter	12.7 mm
Outside diameter	34.925 mm
Thickness	19.05 mm
Weight	160 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE