


Cam follower CR24-VUU-IKO - CR24-VUU-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cr24-vuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



CR-VUU

Stud dia. mm (inchi)	Identification number				Mass (Ref.)					
	Shield type		Sleeved type		ϕ	D	C	d_1	G	G_1
15.875 ($\frac{5}{8}$)	With covered outer ring	With cylindrical outer ring	With drilled outer ring	With cylindrical outer ring					UNF	
				CR 24 VUU	230	38.100 ($\frac{1}{2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	$\frac{1}{2}$ -18	18.050 ($\frac{7}{8}$)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C	Basic static load rating C_0		
B max	B ₂	B ₃	C ₁	ϕ ₁					ϕ ₂	r
22.8 (0.90)	38.100 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{4}$)	4.762 ($\frac{3}{8}$)	3.969 ($\frac{5}{16}$)	1.588 ($\frac{1}{4}$)	28.166 (1.1)	55.7	28 200	40 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463890
Inside diameter	15.875 mm
Outside diameter	38.1 mm
Thickness	22.225 mm
Weight	230 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE