


## Cam follower CR24-VBUUR-IKO - CR24-VBUUR-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cr24-vbuur-iko>

IKO

**CAM FOLLOWERS**

Inch Series Cam Followers **With Cage/With Screwdriver Slot**



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With groove outer ring	Shield type With cylindrical outer ring							
15.875 ( $\frac{5}{8}$ )			<b>CR 24</b>	<b>VBUUR</b>	230	38.100 ( $\frac{1}{2}$ )	22.225 ( $\frac{7}{8}$ )	15.875 ( $\frac{5}{8}$ )	$\frac{1}{4}$ -18	19.050 ( $\frac{3}{4}$ )	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
23.8 (0.93)	38.100 ( $\frac{1}{2}$ )	9.525 ( $\frac{3}{8}$ )	0.794 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{16}$ )	3.969 ( $\frac{1}{8}$ )	7.938 ( $\frac{1}{4}$ )	1.588 ( $\frac{1}{16}$ )	26.195 ( $\frac{1}{2}$ )	55.7	29 200	40 100

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463920
Inside diameter	15.875 mm
Outside diameter	38.1 mm
Thickness	22.225 mm
Weight	230 g
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE