


Cam follower CR32-V-IKO - CR32-V-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cr32-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inchi)	Identification number				Mass (Ref.)					
	Shield type		Sleeved type		ϕ	D	C	d_1	G UNF	G_1
	With covered outer ring	With cylindrical outer ring	With drilled outer ring	With cylindrical outer ring						
22.225 ($\frac{7}{8}$)		CR 32 V			627	50.800 (2)	31.750 (1 $\frac{1}{2}$)	22.225 (7 $\frac{1}{8}$)	$\frac{1}{4}$ -14	25.400 (1)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N		
B max	B_2	B_3	C_1	g_1					g_2	r
33.5 (1.32)	50.800 (2)	12.700 (1/2)	0.794 (1/32)	4.762 (3/8)	4.762 (3/8)	1.588 (1/8)	31.268 (1 1/8)	162	45 700	80 800

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464187
Inside diameter	22.225 mm
Outside diameter	50.8 mm
Thickness	31.75 mm
Weight	627 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE