


Cam follower CRH26-V-IKO - CRH26-V-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/crh26-v-iko>

IKO

CAM FOLLOWERS

Inch Series Heavy Duty Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number		Mass (Ref.) g	D	C	d ₁	G LINE	G ₁	B max
	Shield type	Sealed type							
22.225 ($\frac{7}{8}$)	CRH 26	V	329	41.275 ($1\frac{5}{8}$)	22.225 ($\frac{7}{8}$)	22.225 ($\frac{7}{8}$)	$\frac{1}{4}$ -14	19.050 ($\frac{3}{4}$)	24.318
Boundary dimensions mm(inch)				Mounting dimension f mm(inch)	Maximum spring C	Basic dynamic load rating C	Basic static load rating C ₀		
B ₂	B ₃	C ₁	s ₁					s ₂	r
38.100 ($1\frac{1}{2}$)	8.525 ($\frac{1}{2}$)	1.588 ($\frac{1}{8}$)	4.782 ($\frac{3}{8}$)	2.381 ($\frac{3}{16}$)	1.588 ($\frac{1}{8}$)	26.988 ($1\frac{1}{8}$)	182	28 200	40 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464651
Inside diameter	22.225 mm
Outside diameter	41.275 mm
Thickness	22.225 mm
Weight	329 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE