

SI Rod end SI18-T-K-DURBAL - SI18-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/si18-t-k-durbal>

SI18-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
SI 18 TIK			d	G	B	C ₁	d ₂	d ₃	d ₄
			18	M 18 x 1,5	23	16,50	44	25,0	31

type	measurement [mm]			d ₁ PT	load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h			
SI / SI18 TIK	32	27	71	15	47,5	0,320

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489520
Inside diameter	18 mm
Outside diameter	44 mm
Thickness	23 mm
Type	SI
Weight	320 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE