

## SI Rod end SIL20-T-K-DURBAL - DSIL20-T-K-DURBAL

https://www.123bearing.ca/bearing-housing/rod-end/si/dsil20-t-k-durbal


### SIL20-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
SIL 20 T/K			d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
			20	M 20 x 1,5	25	18,00	50	27,5	34

type	measurement [mm]			h	d <sub>1</sub> PT	load rating C <sub>10</sub> [N]	weight [kg]
	l <sub>3</sub> min	W					
SI / SIL 20 T/K	33	30	77	14	57,0	0,420	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489568
Inside diameter	20 mm
Outside diameter	50 mm
Thickness	25 mm
Type	SI
Weight	420 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE