

SI Rod end SIL30M27X2-T-K-DURBAL - DSIL30M27X2-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/dsil30m27x2-t-k-durbal>


SIL30M27X2-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIL 30 TIK M 27 X 2			30	M 27 x 2	37	25,00	70	40,0	50

type	measurement (mm)			d1	load rating C0 (N)	weight (kg)
	l1 min	W	h			
SI / SIL 30 TIK M 27 X 2	51	41	110	17	114,0	1,100

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489735
Inside diameter	30 mm
Outside diameter	70 mm
Thickness	37 mm
Type	SI
Weight	1100 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE