

SI Rod end SI30M27X2-T-K-DURBAL - SI30M27X2-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/si30m27x2-t-k-durbal>


SI30M27X2-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated

sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 30 TIK M 27 x 2			30	M 27 x 2	37	25,00	70	40,0	50

type	measurement (mm)			d1	load rating C0 [N]	weight [kg]
	l1 min	W	h			
SI / SIL 30 TIK M 27 x 2	51	41	110	17	114,0	1,100

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489766
Inside diameter	30 mm
Outside diameter	70 mm
Thickness	37 mm
Type	SI
Weight	1100 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE