

SA Rod end DSAL5-T-K-DURBAL - DSAL5-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/dsal5-t-k-durbal>

DSAL5-T-K



male thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
DSAL 5 T/K		5	M 5	8	6,00	18	

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
DSA / DSAL 5 T/K	19		33	13	6,0	0,013

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489919
Inside diameter	5 mm
Outside diameter	18 mm
Thickness	8 mm
Type	SA
Weight	13 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE