


## SA Rod end DSAL6-T-K-DURBAL - DSAL6-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/dsal6-t-k-durbal>

### DSAL6-T-K



**male thread:**  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
DSAL 6 T/K		6	M 6	9	6,75	20	
type	l <sub>1</sub> min	measurement [mm]		h	α	Tragzahlen C <sub>10</sub> [kN]	weight [kg]
DSA / DSAL 6 T/K	21	l <sub>1</sub>	l <sub>2</sub>	36	13	7,7	0,020

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489940
Inside diameter	6 mm
Outside diameter	20 mm
Thickness	9 mm
Type	SA
Weight	20 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE