

SA Rod end
SA50-T-K-DURBAL - SA50-T-K-DURBAL
<https://www.123bearing.ca/bearing-housing/rod-end/sa/sa50-t-k-durbal>


SA50-T-K



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]				
	d	G	B	C ₁	d ₂
SA 50 T/K	50	M 48 x 2	60	45,00	117

type	measurement [mm]			Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂	h		
SA / SAL 50 T/K	105	59	185	12	4,800

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490526
Inside diameter	50 mm
Outside diameter	117 mm
Thickness	60 mm
Type	SA
Weight	4800 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE