

## SA Rod end DSSA5-T-K-DURBAL - DSSA5-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/dssa5-t-k-durbal>

### DSSA5-T-K



**male thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	right hand thread	left hand thread	measurement [mm]				
DSSA 5 T/K	S	M 5	B	C1	d2	G	
			8	6,00	18		

type	measurement [mm]			load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub> min	h		
DSSA / DSSAL 5 T/K	19		33	6,0	0,013

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490533
Inside diameter	5 mm
Outside diameter	18 mm
Thickness	8 mm
Type	SA
Weight	13 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE