

SA Rod end SSA8-T-K-DURBAL - DSSA8-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/dssa8-t-k-durbal>

SSA8-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]				
SSA 8 T/K	8	M 8	12	9,00	24		

type	measurement [mm]		h	alpha [°]	load rating C ₀ [kN]	weight [kg]
	i, min	i ₂ min				
SSA / SSAL 8 T/K	25	42	14	12,9	0,038	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490625
Inside diameter	8 mm
Outside diameter	24 mm
Thickness	12 mm
Type	SA
Weight	38 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE