

SA Rod end SSA12-T-K-DURBAL - SSA12-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/ssa12-t-k-durbal>

SSA12-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]				
SSA 12 T/K	12		M 12	16	12,00	32	

type	measurement [mm]			load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min	h		
SSA / SSAL 12 T/K	32	54	13	24,0	0,085

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490700
Inside diameter	12 mm
Outside diameter	32 mm
Thickness	16 mm
Type	SA
Weight	85 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE