

SA Rod end SSAL18-T-K-DURBAL - SSAL18-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/ssal18-t-k-durbal>

SSAL18-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]			
SSAL 18 T/K	18		M 18 x 1,5	23	16,50	44

type	measurement [mm]			alpha [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min	h			
SSA / SSAL 18 T/K	41	22	72	15	47,5	0,280

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490823
Inside diameter	18 mm
Outside diameter	44 mm
Thickness	23 mm
Type	SA
Weight	280 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE