

SA Rod end SSAL22-T-K-DURBAL - SSAL22-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/ssal22-t-k-durbal>

SSAL22-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]				
SSAL 22 T/K	22		G	B	C1	d2	
			M 22 x 1,5	28	20,00	54	

type	measurement [mm]			alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min	h			
SSA / SSAL 22 T/K	48	27	84	15	68,0	0,480

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490908
Inside diameter	22 mm
Outside diameter	54 mm
Thickness	28 mm
Type	SA
Weight	480 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE