

SA Rod end SSA25-T-K-DURBAL - SSA25-T-K-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/ssa25-t-k-durbal>

SSA25-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]			
SSA 25 T/K	25		M 24 x 2	31	22,00	60

type	measurement [mm]			alpha [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min	h			
SSA / SSAL 25 T/K	55	30	94	15	85,0	0,640

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490946
Inside diameter	25 mm
Outside diameter	60 mm
Thickness	31 mm
Type	SA
Weight	640 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE