

SA Rod end DSA6-BK-DURBAL - DSA6-BK-DURBAL


https://www.123bearing.ca/bearing-housing/rod-end/sa/dsa6-bk-durbal

DSA6-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel hardened and ground

Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]		measurement [mm]		
	d	G	B	C ₁	d ₂
DSA 6 BK	6	M 6	9	6,7	21

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [g]
	l ₁ min	h			
DSA / DSAL 6 BK	22	36	11	7,65	0,020

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492391
Inside diameter	6 mm
Outside diameter	21 mm
Thickness	9 mm
Type	SA
Weight	20 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE