

SA Rod end SA25-BK-DURBAL - DSA25-BK-DURBAL


<https://www.123bearing.ca/bearing-housing/rod-end/sa/dsa25-bk-durbal>

SA25-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated
Sliding combination:
steel / bronze-PTFE composite
inner ring:
bearing steel hardened and ground
Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite
Lubrication:
maintenance free

order number	measurement [mm]		measurement [mm]				
	right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 25 BK			25	M 24 x 2	31	22,0	61

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
SA / SAL 25 BK	57	94	15	85,00	0,640

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492735
Inside diameter	25 mm
Outside diameter	61 mm
Thickness	31 mm
Type	SA
Weight	640 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE