

SA Rod end GAR10-UK-DURBAL - GAR10-UK-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/gar10-uk-durbal>


GAR10-UK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)					
right hand thread	d	G	B	C1	d2	
GAR 10 UK	10	M 10	9	7,0	29	

type	measurement (mm)		h	alpha [°]	load rating C ₀ (kN)	weight (kg)
	l ₁ min	l ₂ min				
GAR / GAL 10 UK	26	15	48	12	17,6	0,051

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492858
Inside diameter	10 mm
Outside diameter	29 mm
Thickness	9 mm
Type	SA
Weight	51 g
Thread	Right-hand thread
Lubrication	without
Packaging	-
Standard	No standard

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE