

## SA Rod end GAL20-UK-DURBAL - GAL20-UK-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/gal20-uk-durbal>


### GAL20-UK



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	d	G	measurement (mm)	C <sub>1</sub>	d <sub>2</sub>
right hand thread left hand thread <b>GAL 20 UK</b>	20	M 20 x 1,5	16	13,0	53

type	l, min	measurement (mm) l <sub>1</sub> min	h	alpha [°]	load rating C <sub>0</sub> (kN)	weight (kg)
GAR / GAL 20 UK	43	27	78	9	60,0	0,310

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493107
Inside diameter	20 mm
Outside diameter	53 mm
Thickness	16 mm
Type	SA
Weight	310 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE