

## SA Rod end GAL25-UK-2RS-DURBAL - GAL25-UK-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/gal25-uk-2rs-durbal>


### GAL25-UK-2RS



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	d	G	measurement (mm)	C <sub>1</sub>	d <sub>2</sub>
right hand thread left hand thread <b>GAL 25 UK (-2RS)</b>	25	M 24 x 2	20	17,0	64

type	l <sub>1</sub> min	measurement (mm) l <sub>2</sub> min	h	α [°]	load rating C <sub>0</sub> [kN]	weight (kg)
GAR / GAL 25 UK-2RS	53	32	94	7	83,0	0,560

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493145
Inside diameter	25 mm
Outside diameter	64 mm
Thickness	20 mm
Type	SA
Weight	560 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE