

GE Rod end GAR35-UK-2RS-DURBAL - DGAR35-UK-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/ge/dgar35-uk-2rs-durbal>

GAR35-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body ground around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



| order number | measurement (mm) | | | | | |
|-------------------|------------------|----|----------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | s | C ₁ | d ₂ |
| GAR 35 UK-2RS | | 35 | M 36 x 3 | 25 | 21,0 | 82 |

| type | l ₁ min | measurement [mm] l ₂ min | h | α [°] | load rating C ₀ [kN] | weight [kg] |
|---------------------|--------------------|--|-----|-------|------------------------------------|----------------|
| GAR / GAL 35 UK-2RS | 82 | 42 | 140 | 6 | 146,0 | 1,400 |

PRODUCT FEATURES

| | |
|------------------|-------------------|
| Brand | DURBAL |
| N° Ean13 | 3616060467621 |
| Inside diameter | 35 mm |
| Outside diameter | 82 mm |
| Thickness | 25 mm |
| Type | GE |
| Weight | 1400 g |
| Thread | Right-hand thread |
| Lubrication | without |
| Packaging | 1 |
| Standard | No standard |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE