

# GE Rod end GAL60-UK-2RS-DURBAL - DGAL60-UK-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/ge/dgal60-uk-2rs-durbal>


## GAL60-UK-2RS



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	d	G	B	C1	d2
right hand thread left hand thread <b>GAL 60 UK-2RS</b>	60	M 52 x 3	44	38,0	135

type	l1, min	measurement [mm] l2, min	h	a [°]	load rating C0 [kN]	weight [kg]
GAR / GAL 60 UK-2RS	115	75	210	6	450,0	5,900

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3616060467775
Inside diameter	60 mm
Outside diameter	135 mm
Thickness	44 mm
Type	GE
Weight	5900 g
Thread	Left-hand thread
Lubrication	without
Packaging	1
Standard	No standard

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE