

## SI Rod end GIR25-UK-DURBAL - GIR25-UK-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/gir25-uk-durbal>

### GIR25-UK



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Sliding combination:** steel / bronze-PTFE fabric

**Rod end body:** surface zinc plated

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	measurement [mm]					
GIR 25 UK	d	G	B	C <sub>1</sub>	C <sub>2</sub>	d <sub>2</sub> d <sub>4</sub>
	25	M 24 x 2	20	17,0	64	33,5 42
type	measurement [mm]			load rating	weight	
GIR / GIR 25 UK	t <sub>3</sub> min	h	W	C <sub>0</sub> [kN]	[kg]	
	48	94	36	83,0	0,640	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493978
Inside diameter	25 mm
Outside diameter	64 mm
Thickness	20 mm
Type	SI
Weight	640 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE