

SI Rod end GIL60-UK-2RS-DURBAL - GIL60-UK-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/gil60-uk-2rs-durbal>

GIL60-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Sliding combination: steel / bronze-PTFE fabric

Rod end body: surface zinc plated

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

| order number | d | G | B | C ₁ | d ₂ | d ₃ | d ₄ |
|---------------|----|----------|----|----------------|----------------|----------------|----------------|
| GIL 60 UK-2RS | 60 | M 52 x 3 | 44 | 38,0 | 135 | 70,0 | 88 |

| type | measurement [mm] | | | α [°] | load rating C ₀ [kN] | weight [kg] |
|---------------------|--------------------|-----|----|-----------------|---------------------------------------|----------------|
| | t ₃ min | h | W | | | |
| GIR / GIL 60 UK-2RS | 70 | 175 | 75 | 6 | 450,0 | 5,500 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952494258 |
| Inside diameter | 60 mm |
| Outside diameter | 135 mm |
| Thickness | 44 mm |
| Type | SI |
| Weight | 5500 g |
| Thread | Left-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE