

# SI Rod end GIL70-UK-2RS-DURBAL - GIL70-UK-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/gil70-uk-2rs-durbal>

## GIL70-UK-2RS



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
GIL 70 UK-2RS	70	M 56 x 4	49	42,0	160	80,0	98

  

type	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h	W			
GIR / GIL 70 UK-2RS	80	200	85	6	610,0	8,600

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494289
Inside diameter	70 mm
Outside diameter	160 mm
Thickness	49 mm
Type	SI
Weight	8600 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE