

# SI Rod end GIR80-UK-2RS-DURBAL - GIR80-UK-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/gir80-uk-2rs-durbal>

## GIR80-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number	measurement [mm]				
GIR 80 UK-2RS	d 80	G M 64 x 4			
	B 55	C <sub>1</sub> 47,0			
		C <sub>2</sub> 180			
		d <sub>2</sub> 95,0			
		d <sub>3</sub> 110			
		d <sub>4</sub>			
type	measurement [mm]			load rating	weight
GIR / GIL 80 UK-2RS	t <sub>3</sub> min 85	h 230	W 100	C <sub>0</sub> (kN) 750,0	[kg] 12,000

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494326
Inside diameter	80 mm
Outside diameter	180 mm
Thickness	55 mm
Type	SI
Weight	12000 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE