

SA Rod end POS25-DURBAL - POS25-DURBAL


<https://www.123bearing.ca/bearing-housing/rod-end/sa/pos25-durbal>

POS25



Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread; maintenance free, according to DIN ISO 12240-4, series K



Rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required

order number	right hand thread		left hand thread		measurement [mm]		
	G	M 24 x 2	B	C1	d1		
POS 25	25	M 24 x 2	31	22,00	60		

type	measurement [mm]		α [°]	load rating C0 [kN]	weight [kg]
	l1 min	h			
POS / POSL 25	57	94	15	68,0	0,640

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494777
Inside diameter	25 mm
Outside diameter	60 mm
Thickness	31 mm
Type	SA
Weight	640 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE