

## SI Rod end SIZJ12-DURBAL - SIZJ12-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/sizj12-durbal>

### SIZJ12



**female thread:**  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches

**Description:** DIN ISO rod end K series. Dimensions  
in inch. Sliding combination steel / steel.  
Size  $\geq 9$  with grease nipple can be mounted upon  
request.

**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required

order number	d	B	C <sub>1</sub>	d <sub>2</sub>	G	d <sub>3</sub>	d <sub>4</sub>
SIZJ 12	12,70	15,88	11,50	33,32	1/2 - 20	18,67	22,23

  

type	inches	h <sub>1</sub> min	W	h	$\alpha$ [°]	load rating C <sub>0</sub> (kN)	weight (kg)
SIZJ / SIZJL 12	1 / 2 "	25,40	19,05	53,98	10,0	28,0	0,132

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496870
Inside diameter	12.7 mm
Outside diameter	33.32 mm
Thickness	15.88 mm
Type	SI
Weight	132 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE