

SI Rod end SIZJ15-DURBAL - DSIZJ15-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/dsizj15-durbal>

SIZJ15



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon
request.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

| order number | right hand thread | left hand thread | measurement [mm] | | | | | |
|----------------|-------------------|------------------|------------------|----------------|----------|----------------|----------------|--|
| | d | B | C ₁ | d ₂ | G | d ₃ | d ₄ | |
| SIZJ 15 | 15,88 | 19,05 | 12,29 | 38,10 | 5/8 - 18 | 21,84 | 25,40 | |

| type | inches | h ₁ min | measurement [mm] | | α | load rating | weight |
|------------------------|---------------|--------------------|------------------|-------|------|------------------------|--------|
| | | | W | h | [°] | C ₀ [kN] | [g] |
| SIZJ / SIZJL 15 | 5 / 8" | 31,75 | 22,23 | 63,50 | 13,0 | 29,0 | 0,195 |

PRODUCT FEATURES

| | |
|------------------|-------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952496900 |
| Inside diameter | 15.88 mm |
| Outside diameter | 38.1 mm |
| Thickness | 19.05 mm |
| Type | SI |
| Weight | 195 g |
| Thread | Right-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE