

SI Rod end SIZJL15-DURBAL - SIZJL15-DURBAL

https://www.123bearing.ca/bearing-housing/rod-end/si/sizjl15-durbal

SIZJL15



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon
request.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number	right hand thread	left hand thread	measurement [mm]					
SIZJL 15	15,88	19,05	12,29	38,10	5/8 - 18	21,84	25,40	

type	inches	h ₁ min	measurement [mm]		α	load rating	weight
			W	h	[°]	C ₀ [kN]	[g]
SIZJ / SIZJL 15	5 / 8"	31,75	22,23	63,50	13,0	29,0	0,195

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496917
Inside diameter	15.88 mm
Outside diameter	38.1 mm
Thickness	19.05 mm
Type	SI
Weight	195 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE