

SI Rod end SI20-ES-2RS-DURBAL - DSI20-ES-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/dsi20-es-2rs-durbal>

SI20-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 20 ES (-2RS)		20	M 20 x 1.5	16	13,0	53	27,5	35

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SIL 20 ES (-2RS)	40	32	77	9	60,0	0,35

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497105
Inside diameter	20 mm
Outside diameter	53 mm
Thickness	16 mm
Type	SI
Weight	350 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE