

SI Rod end SI30-ES-DURBAL - SI30-ES-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/si30-es-durbal>

SI30-ES



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 30 ES		30	M 30 x 2	22	19,0	73	40,0	50

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SII 30 ES	56	41	110	6	110,0	0,93

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497235
Inside diameter	30 mm
Outside diameter	73 mm
Thickness	22 mm
Type	SI
Weight	930 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE