

SI Rod end SIL45-ES-2RS-DURBAL - DSIL45-ES-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/dsil45-es-2rs-durbal>

SIL45-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSIL...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIL 45 ES (-2RS)		45	M 42 x 3

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SIL 45 ES (-2RS)	65	60	145	7	240,0	2,5

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497464
Inside diameter	45 mm
Outside diameter	102 mm
Thickness	32 mm
Type	SI
Weight	2500 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE