

# SI Rod end SI50-ES-2RS-DURBAL - SI50-ES-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/si50-es-2rs-durbal>

## SI50-ES-2RS



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**order number**  
right hand thread    left hand thread

SI 50 ES (-2RS)	measurement (mm)	
	d	G
	50	M 45 x 3

type	measurement [mm]		h	$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W				
SI / SII 50 ES (-2RS)	68	65	160	6	290,0	3,5

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497549
Inside diameter	50 mm
Outside diameter	112 mm
Thickness	35 mm
Type	SI
Weight	3500 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE