

SI Rod end SI60-ES-2RS-DURBAL - SI60-ES-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/si60-es-2rs-durbal>

SI60-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

| order number | | measurement (mm) | | | | | | |
|-------------------|------------------|------------------|----------|----|------|-----|------|----|
| right hand thread | left hand thread | d | G | B | C1 | d2 | d3 | d4 |
| SI 60 ES (-2RS) | | 60 | M 52 x 3 | 44 | 38,0 | 135 | 70,0 | 88 |

| type | measurement [mm] | | | α [°] | load rating C_0 [kN] | weight [kg] |
|-----------------------|------------------|----|-----|--------------|------------------------|-------------|
| | l_1 min | W | h | | | |
| SI / SII 60 ES (-2RS) | 70 | 75 | 175 | 6 | 450,0 | 5,5 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | DURBAL |
| N° Ean13 | 3663952497679 |
| Inside diameter | 60 mm |
| Outside diameter | 135 mm |
| Thickness | 44 mm |
| Type | - |
| Weight | 5500 g |
| Thread | - |
| Lubrication | - |
| Packaging | - |
| Standard | - |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE