

## SA Rod end SAL25-ES-2RS-DURBAL - SAL25-ES-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/sal25-es-2rs-durbal>

### SAL25-ES-2RS



**male thread: lubrication is necessary, according to DIN ISO 12240-4, series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.

**Ball end body:** surface zinc plated

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
	SAL 25 ES (-2RS)	25	M 24 x 2	20	17,0	64

type	measurement [mm]				n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h				
SA / SAL 25 ES (-2RS)	53	32	94		7	83,0	0,560

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498270
Inside diameter	25 mm
Outside diameter	64 mm
Thickness	20 mm
Type	SA
Weight	560 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE