

## SA Rod end SA40-ES-2RS-DURBAL - SA40-ES-2RS-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/sa40-es-2rs-durbal>

### SA40-ES-2RS



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.


Ball end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 40 ES (-2RS)		40	M 39 x 3	28	23,0	92

type	measurement [mm]			n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h			
SA / SAL 40 ES (-2RS)	86	46	150	7	180,0	1,800

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498508
Inside diameter	40 mm
Outside diameter	92 mm
Thickness	28 mm
Type	SA
Weight	1800 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE