

SA Rod end SAL50-ES-DURBAL - SAL50-ES-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/sal50-es-durbal>

SAL50-ES



male thread: lubrication is necessary, according to DIN ISO 12240-4, series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication is necessary

| order number | | measurement [mm] | | | | |
|-------------------|------------------|------------------|----------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| | SAL 50 ES | 50 | M 45 x 3 | 35 | 30,0 | 112 |

| type | measurement [mm] | | | | n [°] | load rating C ₀ [kN] | weight [kg] |
|----------------|--------------------|----------------|-----|--|-------|---------------------------------|-------------|
| | l ₁ min | l ₂ | h | | | | |
| SA / SAL 50 ES | 107 | 56 | 185 | | 6 | 290,0 | 3,400 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952498706 |
| Inside diameter | 50 mm |
| Outside diameter | 112 mm |
| Thickness | 35 mm |
| Type | SA |
| Weight | 3400 g |
| Thread | Left-hand thread |
| Lubrication | with |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE