

TAPR Rod end GIHO-KL-20DO-DURBAL - DGIHO-KL-20DO-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/tapr/dgiho-kl-20do-durbal>

GIHO-KL-20DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	
GIHO-KL 20 DO*		20	24,1	55	M 14 x 1,5	25	55	16	13	17	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 20 DO	58	19	85,5	25	9	42,5	0,43

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500690
Inside diameter	20 mm
Outside diameter	55 mm
Thickness	13 mm
Type	TAPR
Weight	430 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE