

# TAPR Rod end GIHO-KL-30DO-DURBAL - GIHO-KL-30DO-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/tapr/giho-kl-30do-durbal>

## GIHO-KL-30DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number	measurement [mm]	
right hand thread	left hand thread	
GIHO-KL 30 DO		
	30	34,2 80 M 20 x 1,5 36 77 22 19 19

type	measurement [mm]				$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	$h_1$	$l_1$	$l_2$	$l_3$			
GIHO-K / GIHO-KL 30 DO	85	29	125,0	35	6	108,0	1,25

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500775
Inside diameter	30 mm
Outside diameter	80 mm
Thickness	19 mm
Type	TAPR
Weight	1250 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE