

TAPR Rod end GIHO-KL-60DO-DURBAL - GIHO-KL-60DO-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/tapr/giho-kl-60do-durbal>

GIHO-KL-60DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	measurement [mm]	
right hand thread	left hand thread	
GIHO-KL 60 DO		
	d	d ₁ d ₂
	60	66,8 160
	M	42 x 2
	G	d ₃ d ₄ B C ₁ C ₂
	68	134 44 38 38

type	measurement [mm]			load rating	weight
	h ₁	l ₁	l ₂	C ₀ [kN]	[kg]
GIHN-K / GIHN-KL 60 DO	150	57	230,0	68	7,15

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500881
Inside diameter	60 mm
Outside diameter	160 mm
Thickness	38 mm
Type	TAPR
Weight	7150 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE