

SI Rod end PF10-00-502-DURBAL - PF10-00-502-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/pf10-00-502-durbal>

PF10-00-502



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1


lubrication fitting:
DIN 3485 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread;
long-term lubrication, low maintenance, shields



order number		measurements [mm]										
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃	
PF 10 -00		-502	10	15	M 8	13,0	30	13,0			9	
			measurements [mm]				weight	calculation factors	rotational speed limit	basic load rating		
type	h	l	r	SW	α	γ	Y	‰	f_{max} [min]	C	C ₁₀	C ₅₀
PF 10	38	17	14,5	10	13	7,0	0,063	1,90	1,81	1225	2605	985

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507378
Inside diameter	10 mm
Outside diameter	30 mm
Thickness	13 mm
Type	SI
Weight	63 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE