

## SA Rod end PM06-02-501-DURBAL - PM06-02-501-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/pm06-02-501-durbal>

### PM06-02-501



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating	
type	type	d <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>	d <sub>5</sub>	Y	Y <sub>c</sub>	n <sub>max</sub> [min <sup>-1</sup> ]	C	C <sub>0</sub>	stat. [N]
PM 06 -02 -501		6	M 10 x 1	8,5	24	1,28	1,34	1300	2445	765	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507491
Inside diameter	6 mm
Outside diameter	24 mm
Thickness	14 mm
Type	SA
Weight	57 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE