

SA Rod end PM17-01-501-DURBAL - PM17-01-501-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/pm17-01-501-durbal>

PM17-01-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/AH1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]						
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3			
PM 17 -01	-501	17	M 20 x 1,5	21,0	48	25	22	16					
measurements [mm]		weight	calculation-factors		rotational speed limit	basic load rating		stat.					
type	l1	l2	l3	h1	h2	u	z	alpha [°]	Y	Yc	nmax [min-1]	C [N]	C0 [N]
PM 17	36	36	78,5	3,5	2,5	7,0			2,35	2,46	875	5575	2680

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507699
Inside diameter	17 mm
Outside diameter	48 mm
Thickness	22 mm
Type	SA
Weight	354 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE